

**KOVOBEL****Špecifikácie/Specification P6018D****HAN'S LASER**

MODEL	P6018D	P6010D	P10018D
TUBE PROCESSING AREA	6200mm x □ 20-180mm, 6200mm x ○ 20-180mm	6200mm x □ 20-100mm, 6200mm x ○ 20-100mm	10200mm x □ 20-180mm, 10200mm x ○ 20-180mm
BEVEL ANGLE AREA	N/A	N/A	N/A
X AXIS TRACK	6750 mm	6750 mm	10700 mm
Y AXIS TRACK	200 mm	200 mm	200 mm
Z AXIS TRACK	160 mm	160mm	160mm
A,B,C AXIS TRACK	Limitless Rotation (without C Axis)	Limitless Rotation (without C Axis)	Limitless Rotation (without C Axis)
X,Y MAX. POSITIONING SPEED	100 m/min	100 m/min	100 m/min
A,B,C MAX. ROTATING SPEED	120 rpm	120 rpm	120 rpm
X,Y AXIS POSITIONING ACCURACY	+/-0.03mm/1000mm	+/-0.03mm/1000mm	+/-0.03mm/1000mm
CNC SYSTEM	HANS 701 Pro	HANS 701 Pro	HANS 701 Pro
MAX. LOAD OF WORKTABLE	100 kg	100 kg	100 kg
MACHINE TOOL WEIGHT	12 000 kg	11 000 kg	14 000 kg
LOADING LENGTH	3000-6200 mm	3000-6200 mm	4000-10200 mm
UNLOADING LENGTH	0-4000 mm	0-2000 mm	0-4000 mm
PHASE/POWER/FREQUENCY	3/380V/50Hz	3/380V/50Hz	3/380V/50Hz
IP DEGREE	IP54	IP54	IP54
DIMENSION (LxWxH)	1300MM x 4500mm x 3000mm	11000mm x 4500mm x 2800mm	12000mm x 5000mm x 2870mm